



CNB-M-S600

- 1/3" Format CCD Imager
- Ultra High Resolution : 600 TV Lines
(BW 650TV Lines)
- Fixed Lens(f=3.8mm)
- Min. Illumination : 0.1Lux
- Auto White Balance
- AGC, SBLC, Flickerless
- 3-Axis Movement for Free Lens Rotation
- 85m Dome Size

» Hi-Res Image down



Specification

► Drawing

Model	DFL-20S	DFL-21S
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734 KHz	15.625kHz
Scanning Frequency(V)	59.94 Hz	50Hz
Image Sensor	1/3 inch Format CCD Imager	
Sync. System	Internal	
Total Pixels Number	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	600 TV Lines (BW 650TV Lines)	
Video Output Level	1.0 Vp-p (75 \diamond \diamond , Composite)	
S/N Ratio	More than 50dB (AGC Off)	
Lens	Fixed Lens (f=3.8mm, 6.0mm Selectable) *Optional (f=2.45mm, Smoke Cover)	
Min. Illumination	0.1 Lux	
White Balance	Auto	
AGC	Auto	
SBLC	Auto	
Electronic Shutter Speed	1/60~1/120,000	1/50~1/120,000
Operating Temperature	-10 \diamond \diamond C~45 \diamond \diamond C / Humidity 30%~80% RH	
Power Voltage	12VDC (10V~15V)	
Power Consumption	Max. 1.8W/150mA	
Dimensions	113.2 x 79.15 mm	
Weight (Net)	Approx. 210g	