



» Hi-Res Image down

zoom

## CNB-MI-600

- 1/3" SONY Super HAD CCD ◆◆
- Ultra High Resolution : 600 TV Lines  
(BW 650TV Lines)
- Built-in DC Iris Vari-focal Lens(f=2.8~10.5mm)
- TDN(ICR), DNR
- Min. Illumination : 0.01Lux (B/W)
- OSD, Auto White Balance
- AGC, SBLC, Flickerless
- Motion Detection, Privacy Zone, Mirror Function
- 3-Axis Movement for Free Lens Rotation
- 92m Dome Size
- (Option) RS-485(Pelco-D, CNB) Interface

### Specification

► Drawing

► Optional Accessories

► Option model

Model	DBM-20VF	DBM-21VF
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734 KHz	15.625kHz
Scanning Frequency(V)	59.94 Hz	50Hz
Image Sensor	1/3 inch SONY Super HAD CCD ◆◆	
Sync. System	Internal	
Total Pixels Number	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	600 TV Lines (BW 650TV Lines)	
Video Output Level	1.0 Vp-p (75◆◆, Composite)	
S/N Ratio	More than 50dB (AGC Off)	
Lens	DC Iris Vari-focal Lens (f=2.8~10.5mm)	
Min. Illumination	0.1 Lux (Color), 0.01 Lux (B/W)	
Day & Night System	ICR(AGC Type)	
Digital Noise Reduction (SDNR)	Low, Middle, High, Off	
White Balance	ATW, Manual, Push	
AGC	On/Off	
SBLC	Off, Low, Middle, High	

Flickerless	On/Off	
OSD Menu	English, Chinese	
Mirror Function	Horizontal	
Privacy Zone	On/Off (4 Programmable Zone)	
Motion detection	On/Off (4 Programmable Zone)	
Electronic Shutter Speed	1/60~1/120,000	1/50~1/120,000
Manual Shutter Speed	1/60, 1/250, 1/700, 1/1K, 1/1.6K, 1/2.5K, 1/5K, 1/7K, 1/10K, 1/30K, 1/60K, 1/120K	1/50, 1/250, 1/700, 1/1K, 1/1.6K, 1/2.5K, 1/5K, 1/7K, 1/10K, 1/30K, 1/60K, 1/120K
Power Voltage	12VDC (10V~15V)	
Power Consumption	Max. 2.2W/180mA	
Dimensions	123 x 95 mm	
Weight (Net)	Approx. 366g	