



CNB-PTZ-O

- 270x Zoom(27x Optical / 10x Digital)
- User Friendly Installation
- An angle of direction display
- 128 preset positions
- Pan/tilt maximum rotating speed is 360°/sec
- Electronic sensitivity-up (DSS)
- True Day & Night (ICR)
- Auto focus, Auto parking functions
- Automatic Flip Function
- Privacy masking function
- RS-485 protocol compatible
- IP66

▶ Feature

Specification

▶ Drawing

▶ Option model

Model	SS2765NW	SS2765PW
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734kHz	15.625kHz
Scanning Frequency(V)	59.94Hz	50Hz
Image Sensor	1/4" SONY Super HAD Interline transfer CCD	
Sync. System	Internal/Line-Lock	
Total Pixels Number	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	480 TV Lines	
Video Output Level	1.0Vp-p (75Ω, composite)	
S/N Ratio	More than 48dB (AGC off)	
Min. Illumination	1.0lx (color), 0.5lx (BW), 0.001lx (DSS 128FLD) 30IRE	
Day & Night System	Electronic sensitivity-up (DSS), TDN(ICR)	
White Balance	Auto/Manual(Red, Blue Gain Adjustable)	
OSD Menu	On/Off	

Privacy Zone	On/Off(8 zone settings)	
Electronic Shutter Speed	1/60~1/10,000sec	1/3~1/10,000sec
Preset	128 positions with labels	
Swing	8 swings	
Pattern	4 patterns (about 5min/pattern)	
Group	8 groups (max. 20 entries)	
Panning/Tilting Range	Pan: 360° endless rotation; Tilt: 90°	
Panning/Tilting Speed	Manual: 1° ~ 360°/sec; Preset: 360°/sec; Swing: 1°~180°/sec	
Power Voltage	24VAC/1A	
Power Consumption	14.4W	
Dimensions	Dome: 149(Ø); Housing: 249(Ø) x 355.4(H) mm	
Weight (Net)	Main Body : Approx. 4.3kg(with Sun-sheild), Pendant Mount : Approx. 1.9kg	